



Multi-Storey Commercial Buildings in Steel

Bassam Bugan
SCI Director
Kiev, 6 November 2013




SCI

- Established in 1986 to promote the effective use of steel in construction
- Independent member-based organisation
- Staff of 40



29 October 2013






Activities

- Membership
- Technical Information
 - Publications
 - Codes and standards
 - Courses
- Projects
 - Research and Development – Typically new products
 - Engineering Software – Product specific
 - Specialist consultancy – Fire engineering, vibrations, etc.
 - Independent assessment – Product quality

29 October 2013



Multi-storey Buildings in the UK



29 October 2013



Economic Benefits of Steel Construction in Multi-Storey Buildings

- Speed - 20 to 30% reduction in construction time relative to site-intensive construction
- Site management costs – 20 to 30% leading to 3-4% saving in overall building cost
- Service integration - reduction of 100-300mm in floor to floor zone and savings in cladding cost
- Foundations - 30% reduction in overall foundation loads compared with R.C.
- Column free space - more flexible use of space

29 October 2013



Multi-Storey Office Buildings

- Framing
- Floor systems
- Service integration
- Fire resistance

29 October 2013



Structural Form

- Braced frame
 - Steel bracing – buildings up to 6 storeys high
 - Concrete core – building >6 storeys
- Continuous frame (moment connections)
 - Used in buildings up to 4 storeys
 - Typically where bracing needs to be eliminated due to highly glazed facades

29 October 2013



Braced Frame – steel bracing



29 October 2013




Braced Frame – concrete core



29 October 2013



Braced Frame – Concrete Core




© 2013 SCI, All Rights Reserved

29 October 2013



Braced Frame - connections




- Simplicity
- Standardisation

29 October 2013



Composite Floor Construction


- Composite decking
 - Shallow decking
 - Deep decking
- Composite beams
 - Downstand beams
 - Shallow floor solutions
 - Long span solutions



29 October 2013




Trapezoidal Composite Decking



29 October 2013



“Re-entrant Corner” Composite Decking



29 October 2013



Deep Decking



Downstand composite beam with composite shallow deck



Shallow floor beam with deep composite deck

29 October 2013



Deck Span Ranges

Deck Profile	Span (m)	Slab Depth (mm)
≤ 50 mm	2.5 – 3.2	100 – 130
50 – 60 mm	3.2 – 3.8	130 – 150
80 mm	3.8 – 4.5 m	150 – 180
146 mm	5.0 – 6.5 m	215 – 305
225 mm	5 – 8 m	300 – 350

29 October 2013




Performance Verified by Testing



29 October 2013



Long Span Composite Floors




Long span composite beam with composite shallow deck

29 October 2013



Steel Beams in Composite Floors




Slim floor beam

Integrated floor beams

29 October 2013



Typical Span Ranges



29 October 2013




Advantages of Composite Construction

- Composite beams are stronger and stiffer than steel beams
 - Steel weight reduced by typically 30 to 50%
 - Reduction in beam depth (span:depth ≈ 25)
 - Lightweight construction
 - Improved vibration and fire resistance
- Composite slabs are more efficient than RC slabs
 - Decking acts as working platform
 - Decking stabilises the beams
 - Composite slabs are fire resistant

29 October 2013



Service Integration



29 October 2013







UK Fire Resistance Requirements

Table A.2 of Approved Document B

Maximum height, m.	Approximate number of storeys	Office	
		Without Sprinklers	With Sprinklers
> 30m		Not Permitted	120
≤ 30m	10	90	60
≤ 18m	6	60	30
≤ 5m	1 to 2	30	30

Fire resistance period: time required for a building to retain its load carrying capacity to enable evacuation of the building

UK Fire Resistance (Risk Based)


Building Description*	Approved Document B (mins)	BS 9999 without sprinklers (mins)	BS 9999 with sprinklers (mins)
Open plan office building, 2 storey and less than 1000m ² ground floor area.	30	15*	15*
Open plan office building over 30 metres but less than 60 metres in height.	120 plus sprinklers	90†	60
3 storey Department store.	60	45	30
Department store between 11 and 18 metres in height.	60	75	60
Medium risk, 4 storey storage.	90	90	60
Leisure centre, 2 storey.	60	30	30

* Height is measured from ground to the height of the floor of the top storey
 † Most steel members can achieve 15 minutes fire resistance without added protection
 ‡ It is unlikely that planning permission would be given without sprinklers

29 October 2013



Fire Resistance of Steel Structures



Fire resistance period is not the length of time that a structure will survive in a fire!

29 October 2013



How Much Fire Protection


Designation	A/V ratio (m ⁻¹)			
Serial size	Profile 3 sides	Profile 4 sides	Box 3 sides	Box 4 sides
457 x 191	161	75	85	60
			60	65

UKBs - 3 sided exposure - indicative data			
A/V	Critical temperature 620°C		
	Dry film thickness (mm) for fire resistance period		
	30 min	60 min	90 min
30	0.265	0.265	0.420
50	0.265	0.276	0.494
70	0.265	0.319	0.679
90	0.265	0.357	0.907
110	0.265	0.419	1.099
130	0.286	0.487	1.300
150	0.299	0.545	1.493
170	0.300	0.626	1.727

29 October 2013




Trends in Fire Protection Materials



29 October 2013



Change in Cost of Fire Protection



29 October 2013



Churchill Plaza, Basingstoke, UK

- 12 storey building
- Built in the 1988
- 90 minutes fire resistance; no sprinklers
- Severe 4 hour fire in 1991
- Fire destroyed 8th and 9th floors and damaged 10th floor



29 October 2013



Churchill Plaza – Fire Damage



29 October 2013



Fire Engineering Research 1994-97



8 storey test building



Bare steel composite beams and deck

29 October 2013



Fire Engineering Research 1994-97



Maximum fire temperature 1213°C
Beam temperature 1100°C
Standard isolated beam in fire test fails at 700°C

29 October 2013




Plantation Place South (London) Fire Engineered Building




A Simplified Fire Engineering Approach (TSLAB)



Heron Tower, London (47 storeys)



The Shard, London (87 storeys)



29 October 2013



SCISteel



SCI Group



www.steel-sci.org

29 October 2013